RoHS2

Industrial waterproof rectangular connector

DK-3 Series（30 Pin）Type

Fujikura



OUTLINE

- ◆ Waterproof rectangular connector was developed for connecting industrial equipment.
- ◆ Crimp termination contacts are the same as those of DK-3000 series.
- ◆ Tab and a receptacle housing are being prepared for the shell shape of the plug, the cable receptacle and the receptacle.
- ◆ DK-3 has one touch locking lever mechanism and a locking supporting system. Pushing contacts in the direction of the mating half makes the connectors automatically and temporarily locked and you can mate the connectors easily.

APPLICATIONS

FA equipment (internal and external), robots, servo motors, medical equipment, communication equipment, OA equipment, various other electrical equipment.

SPECIFICATIONS

Item	DK-3 Series
Rated Voltage	250V AC(r.m.s.) / 600V DC
Rated Current	15A max. / Contact
Dielectric Withstanding Voltage	1,500V AC(r.m.s.)/ 1minute
Insulation Resistance	1,000M Ω min. at 500V DC
Contact Resistance	5m Ω max.
Contact Pitch	5.0mm
Applicable Cable Size	AWG 16 — 28
Waterproof Rating	IP67
Number of Contacts	30 Pin

SAFETY STANDARD

c UL us

TÜVRheinland CERTIFIED
Type Approved
Safety
Regular Production
Surveillance
www.tuv.com
ID 2000000000

Accreditation Organization	Applicable Standards	Certification Number
TUV	DIN VDE 0627 < EN61984 >	R50670485
UL	UL 1977	E72124

MATERIALS / FINISH

RoHS Compliant

Item	Materials / Finishes
Contact	Copper Alloy ／ Au over Ni Plating
Housing	PBT Resin(UL94V-0) ／ Black
Shell / Hood	Aluminum Alloy and Zinc Alloy

◎ Specifications and/or dimenssions in this catalogue are subject to change without notice.
Your catalogue checking the latest speifications with our drawings would be highly appreciated.

Unit : mm

30 Pin Connectors

Plug

DK-3P30E □□ -S(R1)

RC : Receptacle Housing
TC : Tab Housing



Cable Receptacle

DK-3CR30E □□ -S(R1)

RC : Receptacle Housing
TC : Tab Housing



Receptacle

DK-3R30E □□ -S(R1)

RC : Receptacle Housing
TC : Tab Housing



◎ Specifications and/or dimenssions in this catalogue are subject to change without notice.
Your catalogue checking the latest speifications with our drawings would be highly appreciated.

Unit : mm

Crimp Contact

DK-3 Contact

【Contact】

Applicable Cable Size		Insulation O.D. (mm)	Contact Size	Package Style	Part Number		Contact Quantity (pcs)
AWG	mm²				Receptacle Contact	Tab Contact	
28 26 24	0.08 0.12 0.20	0.8 ~ 1.2	S	Reel	DK-3RECSST1-4000	DK-3TABSST1-4000	4,000
		1.0 ~ 1.4		Bag	DK-3RECSLP1-100	DK-3TABSLP1-100	100
24 22 20	0.20 0.30 0.50	1.2 ~ 1.6	M	Reel	DK-3RECMST1-3500	DK-3TABMST1-3500	3,500
		1.7 ~ 2.6		Bag	DK-3RECMLP1-100	DK-3TABMLP1-100	100
20 18 16	0.50 0.85 1.25	1.8 ~ 2.8	L	Reel	DK-3RECLST1-3000	DK-3TABLST1-3000	3,000
		2.2 ~ 2.8		Bag	DK-3RECLLP1-100	DK-3TABLLP1-100	100
16	1.25	2.2 ~ 2.8	2L	Reel	DK-3REC2LST1-3000	DK-3TAB2LST1-3000	3,000
				Bag	DK-3REC2LLP1-100	DK-3TAB2LLP1-100	100

【Premating Contact】

Applicable Cable Size		Insulation O.D. (mm)	Contact Size	Package Style	Part Number		Contact Quantity (pcs)
AWG	mm²				Receptacle Contact	Tab Contact	
24 22 20	0.20 0.30 0.50	1.2 ~ 1.6 1.7 ~ 2.6	M	Bag	DK-3RECMLP1-E-100	DK-3TABMLP1-E-100	100
20 18 16	0.50 0.85 1.25	1.8 ~ 2.8 2.2 ~ 2.8	L	Bag	DK-3RECLLP1-E-100	DK-3TABLLP1-E-100	100
16	1.25	2.2 ~ 2.8	2L	Bag	DK-3REC2LLP1-E-100	DK-3TAB2LLP1-E-100	100

DK-3RECSST1-E-4000

- **Contact Style**
  - REC : Receptacle Contact
  - TAB : Tab Contact
- **Applicable Cable Size**
  - S : AWG 24 — 28
  - M : AWG 20 — 24
  - L : AWG 16 — 20
  - 2L : AWG 16
- **Package Style**
  - ST : Reel
  - LP : Bag
- **Contact Plating**
  - 1 : Au (0.38 μm min) over Ni Plating
- **Contact**
  - E : Premating Contact
  - Omit : Contact
- **Contact Quantity**
  - 4000 : 4000 pcs / Reel
  - 3500 : 3500 pcs / Reel
  - 3000 : 3000 pcs / Reel
  - 100 : 100 pcs / Bag



Tab Contact



Receptacle Contact

Keying Plug 【Prevent Misinsertion Key】

◆ Used to prevent misinsertion.

Part Number : DK-3KP

MOQ : 100 pcs



◎ Specifications and/or dimenssions in this catalogue are subject to change without notice.
Your catalogue checking the latest speifications with our drawings would be highly appreciated.